

Summer  
Special!

# Cool features, at hot prices!



- Heating / Cooling operation at -15°C / -10°C
- A++ rating for cooling mode / A+ for heating mode
- Full inverter 2.5kW (0.9-3.0) and 3.4kW (0.9-3.8) models
- Maximum pipe run of 20m / pre-charged 15m
- ON / OFF Programmable timer
- Powerful, rapid (20min) and super-quiet operation (22dBa)
- Energy saving possible due to 1°C tolerance function



Available through

**FUJITSU**

AIR CONDITIONING

For more product information visit our website [www.fujitsu-general.com/uk](http://www.fujitsu-general.com/uk)

## Specifications

	Indoor	ASYG09LLCC*	ASYG12LLCC*
	Outdoor	AOYG09LLCC	AOYG12LLCC
Nominal Capacity (kW)	Cooling	2.50 (0.90-3.00)	3.40 (0.90-3.80)
	Heating	3.00 (0.90-3.80)	4.00 (0.90-5.00)
Power Consumption (kW)	Cooling	0.73	1.08
	Heating	0.74	1.13
EER / COP (Nominal Conditions)		3.42 / 4.05	3.15 / 3.54
Pdesign (kW) @ -10°C	Cooling	2.50	3.40
	Heating	2.30	3.20
SEER	Cooling	6.90	6.60
SCOP	Heating (Average)	4.00	3.80
Energy Efficiency Class	Cooling	A++	A++
	Heating (Average)	A+	A
Annual Energy Consumption (kWh/a)	Cooling	127	180
	Heating	805	1179
Moisture Removal	l/h	1.30	1.80
Dimensions (HxWxD) mm	Inner	262x820x206	262x820x206
	Outer	535x663x293	535x663x293
Net Weight (kg)	Inner	7	7
	Outer	24	26
Room Air Circulation (high) m3/h	Inner	720	720
	Outer	1670	1830
Power Supply	V-PH-Hz	230 / 1 / 50	230 / 1 / 50
Power Supply To		Outdoor	Outdoor
Running Current (A)	Cooling	3.50	5.20
	Heating	3.50	5.40
Starting Current	A	3.50	5.40
Outdoor Unit Factory Fuse / Suggested MCB/Fuse	A	10	10
Interconnecting Cable		3 + E	3 + E
Remote Control Type		Wireless	Wireless
Sound Pressure (dB(A) Cooling)	Indoor Q/L/M/H	22 / 33 / 38 / 43	22 / 33 / 38 / 43
	Outdoor H	47	50
Sound Power (dB(A) Cooling)	Indoor H	59	59
	Outdoor H	61	65
Max Pipe Length	m	20	20
Max Height Difference	m	15	15
Refrigerant Charge	m	15	15
Additional Refrigerant Charge	g/m	20	20
Pipe Size (inches)	Gas	3/8 (9.52mm)	3/8 (9.52mm)
	Liquid	1/4 (6.35mm)	1/4 (6.35mm)
Operating Range (OC)	Cooling	-10 ~ 43	-10 ~ 43
	Heating	-15 ~ 24	-15 ~ 24
Refrigerant		R410A	R410A

\*Does not include remote control holder. Please use optional part UTZ-RXLA, if required.

The company reserves the right to make any variation in specification to the equipment described or to withdraw or replace products without prior notification or public announcement. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form any part of any contract. All equipment and services are supplied subject to Fujitsu Air Conditioning (UK) Limited's Terms and Conditions of Sale.

All prices shown exclude VAT.



Fujitsu air conditioning products are available from Fujitsu Air Conditioning (UK) Limited and local distributors.

**FUJITSU**  
AIR CONDITIONING